
MODEL GS/S-DC DATA SHEET





TECHNICAL SPECIFICATIONS OF TOOL HOLDERS



The dies (tools) for small parts can be purchased from the button supplier.

Possibility to have custom tool holders.

*VL80 eyelet (for 20") and VL150 eyelet (for 30") were used as reference.

The force required for the application is mentioned in the technical data sheet of the small parts.

PRODUCT DESCRIPTION	Pneumatic press with one head and manual loading.	
USE	Application of snap buttons, eyelets and small parts in general. Piercing of fabrics, leather and plastic sheets.	
TYPE OF START-UP	Pneumatic pedal	
CYLINDER	With diaphragm from 20" With diaphragm from 30"	
CYLINDER FORCE	900 Kg - 8bar	1500 kg - 8 bar
AIR CONSUMPTION PER CYCLE	5,5 N/I a 8 bar	9,0 N/I at 8 bar
APPLICABLE SMALL PARTS SIZE*	Ø max 30 mm	Ø max 50 mm
WORKING PRESSURE	Adjustable 3÷8 bar	
TYPE OF ADJUSTMENT	Pressure reducer with pressure gauge	
PROCESSING TIME	3÷4 " per cycle	
SAFETY	Adjustable hand protection system	
STANDARD EQUIPMENT	4 feet - 1 button tray - 1 double-ended wrench - 1 centering device - one 3 mm Allen wrench	
OPTIONALS	 Red light led positioning device Distance reference guide Suction kit Tool holder panel Approach device Pneumatic timer Custom-made top 	
CERTIFICATION	CE Labeling	
WARRANTY DURATION	12 months	
OPERATING AREA HEIGHT	92 ÷102 cm	
BENCH HEIGHT ADJUSTMENT	Yes	
MACHINE DIMENSIONS	L53xP56xH158÷168 cm	L53xP56xH160÷170 cm
NET WEIGHT	49 kg	50 Kg
PACKAGING MODE	Support disassembled	
STANDARD PACKAGING TYPE	Boxes on pallet	
PACKAGING SIZE	A= 90 cm B = 45 cm C= 84 cm	
	B	C
GROSS WEIGHT	59 Kg	60 kg