

SR-900

SR-1000

FUSING MACHINE 900MM (DOUBLE TEMPERATURE CONTROL) AUTO ADJUST BELT WITH COOLING
 粘合机 900MM(自动调带)(双温控)气动 带冷却

FUSING MACHINE 1000MM (DOUBLE TEMPERATURE CONTROL) AUTO ADJUST BELT WITH COOLING
 粘合机 1000MM(自动调带)(双温控)气动 带冷却



Air Compressor
is Required
需配空压机

- With double cylinder, this machine is with auto adjust belt. Air Pressure of the roller can be adjusted.
- With computer sensor and 2 step motors the belt can be adjusted left and right automatically.
- With double temperature control, you can control the top and lower temperature separately.
- Auto delay stop function to protect the belt life.
- Lower belt is longer than upper belt for easy input of fusing fabric.

- 面料与树脂衬布热熔后, 双缸空气加压, 经传动带输出后立即抽风冷却定型. 具有加压均匀, 气压随时可增减. 工作结束关闭气源后, 保持机器压力滚筒负压状态, 延长机器使用寿命。
- 全自动调整传动带偏带现象(两台进口电机, 进口电器控制调带装置). 走带平稳, 运行可靠。
- 两只温控仪控制上下加热器, 温度均匀。
- 自动延时停机, 延长传动带寿命。
- 进料口加长下传动带, 使操作者更加安全, 投料更加方便。

Model / 型号	SR-900	SR-1000
Fusing Width / 粘合宽度	900 mm	1000 mm
Max. temperature / 最高温度	200 °C	
Max. pressure / 最大压力	4 kg/cm	
Max. belt Speed / 最高带速	8 m/min	
Heater Power / 电热功率	12 kw	15 kw
Motor Power / 电机功率	0.345 kw	
Packing Dimension / 包装尺寸	150 x 116 x 131 cm	170 x 116 x 131 cm
	128 x 90 x 49 cm	135 x 90 x 49 cm
Net Weight / 净重	400 kg	450 kg
Gross Weight / 毛重	530 kg	590 kg