

I 32 M Series

FLATWORK DRYERS IRONERS WITH CYLINDER OF Ø 325



Our range of flatwork ironers I 32 M represents a new concept in improving and speeding up the flatwork drying and ironing process in the industrial laundry area. Our complete offer has been totally renewed and redesigned to cater for the increasingly tougher demands of the laundry and hospitality industry.

The main feature of these machines is that the linen can be fed directly to the flatwork ironer from the high spin washer extractor. They permit a moisture level of up to 45-50% and all in all they provide high-quality ironing, great ergonomics and top performance, combined with easy maintenance and use.

The flatwork dryer ironers I 32 M series is fitted with a roll covered in NOMEX which permits to easily iron any kind of flat linen (padu as tablecloths, napkins, sheets, a.s.o.). The loading and unloading of laundry is front thus allowing also a mural installation.

I 32 M series is available with ELECTRIC or GAS heating system.

The use is particularly recommended for medium size laundries processing also high volumes.

Using a roller with Ø 325 mm in diameter you can obtain a rapid ironing and an optimal drying.

- Outer cabinet in stainless steel.
- Cylinder diameter of Ø 325 mm.
- ELECTRIC or GAS Heating.
- Feeding and ironing belts in NOMEX.
- Polished steel cylinder.
- Electronic Microprocessor for temperature and speed control.
- Automatic control.
- Frequency inverter.
- Steam extractor.
- Can be leaned against the wall.
- Finger Guard protection.
- Frontal inlet and outlet of the linen.

I 32 M Series

Model	Ø Cylinder	Usable Length	Hourly Production	Dimensions L x P x H mm	Net Weight
I 1432 M	Ø 325	mm. 1400	Kg/h. 30 + 20	2050 x 644 x 1107	Kg. 300
I 1632 M	Ø 325	mm. 1600	Kg/h. 30 + 30	2210 x 644 x 1107	Kg. 355
I 2032 M	Ø 325	mm. 2000	Kg/h. 30 + 40	2450 x 644 x 1107	Kg. 405